

HTM64 INFRA RED THERMOSTATIC HOSPITAL TAP



HEALTHCARE



HTM64



0.5 - 5.0 BAR



PRODUCT INFORMATION

HTMWMBCP	Wall mounted infra red thermostatic hospital tap, battery operated
HTMWM MCP	Wall mounted infra red thermostatic hospital tap, mains operated
HTMWMBRS	Wall mounted infra red thermostatic hospital tap, battery operated with detachable spout
HTMWM MRS	Wall mounted infra red thermostatic hospital tap, mains operated with detachable spout

SPECIFICATIONS

WRAS & TMV3 approved
 Full safe touch body
 Thermostatic control
 Integral isolation valves
 Infra red control with 25hr auto hygiene flush
 Smooth internal surfaces
 Sterilisation function for complete tap
 Detachable spout version available for autoclaving
 Flow straightener compliant with HTM64-01
 Lever operated and deck mounted versions available

MATERIAL

Brass

COLOUR/FINISH

Chrome

MANUFACTURER

INTA

FIXING

Panel mounted

APPROVALS

WRAS, HTM64, HTM04-01, TMV3

PRODUCT DIMENSIONS

See technical drawing

ADDITIONAL INFORMATION

Max dynamic pressure 5 bar
 Max static pressure 10 bar
 Min operating pressure 1 bar
 Max inlet temperature 85°C
 Min inlet temperature 10°C
 Pre set factory temperature setting 41°C
 Temperature stability +/- 2°C
 Max temperature differential to ensure failsafe between hot & cold 10°C
 Max unbalanced pressure ration 5:1

